



Safety Data Sheet

SDS date: 05-02-2019

SDS version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Trade Name: Miles Unleaded 95

Product- no.: 1114576, 1114370

CAS no.: 86290-81-5

EINECS no.: 289-220-8

REACH reg. no.: 01-2119471335-39-0011

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: PC13 – Fuel

Manufacture of Low Boiling Point Naphthas, Industrial

Use as an Intermediate, Industrial

Low Boiling Point Naphthas, Industrial

Formulation & (re)packing, Industrial

Use in coatings, Industrial

Use in Cleaning Agents, Industrial

Use as a fuel, Industrial

Use as a fuel, Professional

Use as a fuel, Consumer

Rubber production and processing, Industrial

Uses advised against: This product must not be used for purposes other than those recommended without first seeking the advice of the supplier.

1.3. Details of the supplier of the safety data sheet

Company and address

Circle K Ireland Energy Limited Beech Hill - Clonskeagh, Dublin 4

Ireland

Org. nr. 8209

Tel: Circle K Office: 01 202 8888

Contact person and E-mail:

labsju@circlekeurope.com

The Safety data sheet is completed and validated by:

mediator A/S, Centervej 2, DK-6000 Kolding. Consultant: SJ

1.4. Emergency telephone number

+353 1 808 8232

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

CLP (1272/2008): Flam. Liq. 1;H224, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Muta. 1B;H340, Carc. 1B;H350, Repr. 2;H361fd, Aquatic Chronic 2;H411.

See full text of H-phrases in section 16.

2.1.2.

Physical and chemical hazards: Extremely flammable liquid and vapour. Vapours may form explosive mixtures with air.

Health effect on humans: May cause cancer. May be fatal if swallowed and enters airways. Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain.

Environmental hazards: Toxic to aquatic life with long lasting effects.

2.2. Label elements



Signal word:

Danger

H224 - Extremely flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H336 - May cause drowsiness or dizziness.

H340 - May cause genetic defects.

H350 - May cause cancer.

H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child.

H411 - Toxic to aquatic life with long lasting effects.

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P201 - Obtain special instructions before use.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P501 - Dispose of contents/container in accordance with local regulation.

2.3. Other hazards

This substance is not classified as PBT or vPvB.

According to EU regulation 1907/2006 (REACH)

Additional labelling:

Contains: Gasoline.

Additional warnings:

No data.

SECTION 3: Composition/information on ingredients

3.1./3.2. Substances/Mixtures

Substance	REACH Reg.nr.	CAS nr.	EINECS no.	CLP-classification	w/w%	Note
Gasoline	01-2119471335-39-0011	86290-81-5	289-220-8	Flam.Liq.1;H224, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Muta. 1B;H340, Carc. 1B;H350, Repr. 2;H361fd, Aquatic Chronic 2;H411	≤ 100	1
Ethanol	01-2119457610-43-021/ 01-2119457610-43	64-17-5	200-578-6	Flam.Liq.2;H225, Eye Irrit. 2;H319	0-5	-

1 = Capable of causing cancer.

Note: Gasoline, Low boiling point naphtha – unspecified, contains max. 1%-vol benzene.

See full text of H-phrases in section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

- General:** Remove victim immediately from source of exposure. General first aid, rest, warmth and fresh air. Avoid breathing vapours. Do not get in eyes, on skin, or on clothing.
- Inhalation:** Seek fresh air. Keep victim under observation. Place unconscious person on the side in the recovery position and ensure breathing. Perform artificial respiration if breathing has stopped. Get medical advice/attention.
- Ingestion:** Rinse mouth thoroughly. Drink a few glasses of water or milk. Do not induce vomiting. If vomiting occurs, keep head low so that stomach contents do not enter lungs. Call an ambulance or medical advice.
- Skin contact:** Immediately remove contaminated clothing. Wash skin with soap and water. Seek medical advice in case of persistent discomfort.
- Eye contact:** Flush with water (preferably using eye wash equipment) until irritation subsides. Seek medical advice if symptoms persist.
- Burns:** Flush with water until pain ceases. Remove clothing that is not stuck to the skin – seek medical advice/transport to hospital. If possible, continue flushing until medical attention is obtained.
- Additional information:** When obtaining medical advice, show the safety data sheet or label. Symptoms: See section 11.

According to EU regulation 1907/2006 (REACH)

4.2. Most important symptoms and effects, both acute and delayed

May cause chemical pneumonia if ingested or vomited. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Carcinogenic effects: This product contains substances which are considered or proven to be carcinogenic. The substances are either classified as carcinogenic or as substances thought to be carcinogenic. The danger may lie in inhalation, skin contact or ingestion.

Reproductive toxicity: This product contains substances which can do damage to reproductive capacity, e.g. damage to germ cells or hormonal regulation. The effects can be: sterility, reduced fertility, menstruation disorders, etc.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms such as eczema, dyspnoea, burns or damage to eyes occurs, consult a doctor.

When obtaining medical advice, show the safety data sheet or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Extinguish with powder, foam, carbon dioxide or water mist. Do not use water stream, as it may spread the fire. Use water or water mist to cool non-ignited stock.

5.2. Special hazards arising from the substance or mixture

Avoid inhalation of vapour and fumes – seek fresh air. Product decomposes in fire conditions and toxic gases such as CO and CO₂ may be released. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Fire fighters should use proper protection gear. A closed container, which is exposed to fire, should be cooled with water. Do not allow the water from the fire extinction run into sewer systems and water streams.

5.3. Advice for firefighters

Fire-fighters should wear appropriate protective equipment. Self-Contained Breathing Apparatus (SCBA) and chemical protective suit shall be worn by fire fighters. Water spray should be used to cool containers. Keep run-off water out of sewers and water sources. Send contaminated extinguishing water for destruction.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8 for type of protective equipment. Avoid breathing and contact with skin and eyes. Do not smoke, use open fire or other sources of ignition. Provide adequate ventilation. Warn everybody of potential hazards and evacuate if necessary.

6.2. Environmental precautions

Prevent spillage from entering drains and/or surface water - See section 12. Notify proper authorities in case of contamination of soil or aquatic environment or discharge to drains.

6.3. Methods and material for containment and cleaning up

Contain and absorb spill with sand or other absorbent, non-combustible material and transfer to suitable waste containers. See section 13 for instructions on disposal.

6.4. Reference to other sections

See above.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use the product under well-ventilated conditions, preferably outdoors. Use adequate warning and safety signs to mark areas with risk of exposure to carcinogens or mutagens, including 'No smoking' signs. Running water and eyewashes shall be provided. Washing facilities should be located in the immediate work area. See section 8 for information about precautions for use and personal protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

The product should be stored safely, out of reach of children and away from food, animal feeding stuffs, medicines, etc. Store in a dry, cool, well-ventilated area. Store fireproof. Storage for flammable liquids must follow local regulations for flammable stock.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits according to EH40/2005 Workplace exposure limits (Third edition, 2018):

Substance	Exposure limit (8-hour reference period)	Exposure limit (15-minute reference period)	Note
Ethanol	1000 ppm-1920 mg/m ³	-	-
Benzene	1 ppm – 3.25 mg/m ³	-	BOELV, Sk, Carc 1A

BOELV = Binding Occupational Exposure Limit Values. Sk = Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body. CARC 1A = Substances known to have carcinogenic potential for humans

DNEL and PNEC values:

DNEL – Gasoline (86290-81-5):

Inhalation	Short term (acute)	Systemic effect	Worker	1300 mg/m ³ 15 min
Inhalation	Short term (acute)	Local effect	Worker	1300 mg/m ³ 15 min
Inhalation	Long term (repeated)	Local effect	Worker	840 mg/m ³ 8h
Inhalation	Short term (acute)	Systemic effect	Consumer	1200 mg/m ³ 15 min
Inhalation	Short term (acute)	Local effect	Consumer	640 mg/m ³ 15 min
Inhalation	Long term (repeated)	Local effect	Consumer	180 mg/m ³ 24h

DNEL – Ethanol (64-17-5):

Inhalation	Short term (acute)	Local effect	Worker	1900 mg/m ³ 15 min
Dermal	Long term (repeated)	Systemic effect	Worker	343 mg/kg bw/ day 8h
Inhalation	Long term (repeated)	Systemic effect	Worker	950 mg/m ³ 8h
Inhalation	Short term (acute)	Local effect	Consumer	950 mg/m ³ 15 min
Dermal	Long term (repeated)	Systemic effect	Consumer	206 mg/kg bw/day 8h
Inhalation	Long term (repeated)	Systemic effect	Consumer	114 mg/m ³ 8h
Oral	Long term (repeated)	Systemic effect	Consumer	87 mg/kg bw/ day 8h

PNEC - Gasoline (86290-81-5):

Water	Fresh	2,6 mg/l
Water	Marine	13,8 mg/l

8.2. Exposure controls

See enclosed exposure scenarios for further information.

According to EU regulation 1907/2006 (REACH)

Appropriate engineering controls:

Wash hands before breaks, before using restroom facilities, and at the end of the work. Wear the personal protective equipment specified below.

Personal protective equipment:



Breathing equipment:	<p>Consumer use: Not required.</p> <p>Professional use: Light use (small volume, short exposure (less than 10 minutes): Not required.</p> <p>Medium use (medium volume, medium long-term exposure (> 1 hour): In case of insufficient ventilation, wear respiratory protective equipment with filter AX.</p> <p>Respiratory appliances shall be in compliance with one of the following standards: EN 136/140/145.</p>
Hand protection:	<p>Consumer use: Plastic or rubber gloves recommended.</p> <p>Professional use: Wear protective gloves made of nitrile rubber or neoprene rubber.</p>
Eye protection:	<p>Consumer use: Not required.</p> <p>Professional use: Wear safety goggles if there is a risk of eye splash. Personal eye protection shall comply with EN 166.</p>
Body and skin protection:	<p>Consumer use: Not required.</p> <p>Professional use: Wear suitable protective clothing. possibly wear coveralls.</p>

Environmental exposure controls:

Ensure compliance with local regulations for emissions. Make sure that when using the product damming material is available in immediate vicinity.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	Light yellow liquid
Odour:	Characteristic
Odour threshold:	-
pH:	-
Melting point/ Freezing Point (°C):	< -50
Initial boiling point and boiling range (°C):	25 – 210
Flash point (°C):	< -40
Evaporation rate:	-
Flammability (solid, gas)	-
Upper / lower flammability or explosion limits (vol-%):	1,4 – 7,6
Vapour pressure (mbar, 25 °C):	45 - 100 kPa @ 37 °C
Vapour density (air=1)	-
Relative density:	720 - 775 kg/m ³ @ 15 °C
Solubility(ies):	Not soluble in water
Partition coefficient: n-octanol/water:	> 3
Auto-ignition temperature (°C):	> 250
Decomposition temperature (°C):	-
Viscosity (mm ² /sek):	< 1 mm ² /s @ 40 °C
Explosive properties:	-
Oxidising properties:	-

9.2. Other information

Sulphur content, mass-%:	< 0,001
RON	95,0

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidising agents and strong reducing agents.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions. Emitted vapors can be ignited by a spark, a hot surface or an ember.

10.3. Possibility of hazardous reactions

Product vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Avoid heating and contact with ignition sources.

10.5. Incompatible materials

Avoid contact with strong oxidising agents. Dissolves grease and has an adverse effect on gaskets, some synthetic materials and rubber.

10.6. Hazardous decomposition products

Product decomposes in fire conditions or when heated to high temperatures, and toxic gases such as CO and CO₂ may be released.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute Toxicity: Inhalation of oil spray mist may cause chemical pneumonia.

Substance	Route of exposure	Species	Test	Result
Gasoline	Oral	Rat	LD50 (OECD 401)	>5000 mg/kg
Gasoline	Dermal	Rabbit	LD50 (OECD 402)	>2000 mg/kg
Gasoline	Inhalation	Rat	LC50 (4h) (OECD 403)	>5610 mg/m ³

Skin corrosion/irritation: Irritating to skin – may cause reddening. Degreases and dries the skin. Repeated exposure may cause skin dryness or cracking. Can be absorbed through the skin causing symptoms such as dizziness and headache.

Substance	Route of exposure	Species	Test	Result
Gasoline	-	Rabbit skin	OECD 404	Irritant to skin

Serious eye damage/irritation: Spray and vapour in the eyes may cause irritation and smarting. The effects are expected to be reversible.

Substance	Route of exposure	Species	Test	Result
Gasoline	-	Rabbit Eyes	OECD 405	Non-irritating to the eyes

Respiratory or skin sensitisation: Based on existing data, the classification criteria are deemed not to have been met.

Substance	Route of exposure	Species	Test	Result
Gasoline	-	Guinea pig skin	OECD 406	Not sensitising

Germ cell mutagenicity: May cause genetic defects.

Carcinogenicity: May cause cancer.

Reproductive toxicity: Suspected of damaging fertility. Suspected of damaging the unborn child.

STOT-single exposure: Based on existing data, the classification criteria are deemed not to have been met.

STOT-repeated exposure: Prolonged or repeated exposure by skin contact or inhalation of vapours may cause damage to the central nervous system.

Substance	Route of exposure	Species	Test	Result
Gasoline	Dermal	Rat	NOAEL (OECD 410)	3750 mg/kg/day

Aspiration hazard: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Substance	Test duration	Species	Test	Result
Gasoline	96 h	Fish	LC50	8,2 mg/L
Gasoline	48 h	Daphnia	EC50	4,5 mg/L
Gasoline	72 h	Algae	EC50	3,1 mg/L
Gasoline	-	Fish	-	2,6 mg/L
Gasoline	21 d	Daphnia	NOEC	2,6 mg/L

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
No data	-	-	-

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
Gasoline	Yes	> 3	-

12.4. Mobility in soil

The product has low mobility in soil.

12.5. Results of PBT and vPvB assessment

The product does not meet the criteria for PBT or vPvB.

12.6. Other adverse effects

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Collect spills and waste in closed, leak-proof containers for disposal at the local hazardous waste site.

EWC: depends on industry and use, for example:

Waste code	Waste type
13 07 02	Gasoline
15 02 02	Absorbents, filter materials

Specific labelling

-

Contaminated packaging:

Uncleansed packaging is to be disposed of via the local waste-removal scheme.

According to EU regulation 1907/2006 (REACH)

SECTION 14: Transport information

The product is covered by the rules for transport of dangerous goods.

14.1 -14.4.

Carriage of Dangerous Goods by Road/Rail (ADR/RID)

UN-no.:	Proper shipping name	Transport hazard class(es)	Packing group
1203	GASOLINE	3	II

Carriage of Dangerous Goods by Inland Waterways (ADN)

UN-no.:	Proper shipping name	Environmental hazards	Environmental hazards tanker	Transport hazard class(es)	Packing group
1203	GASOLINE	Yes	N2, CMR, F	3	II

International Maritime Dangerous Goods (IMDG)

UN-no.:	Proper shipping name	Transport hazard class(es)	Packing group
1203	GASOLINE	3	II

Transport of Dangerous Goods by Air (ICAO-TI / IATA-DGR)

UN-no.:	Proper shipping name	Transport hazard class(es)	Packing group
1203	GASOLINE	3	II

14.5. Environmental hazards

If the quantity transported exceeds 5 kg or litre must be labelled with an environmental hazard.



14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Sources:

EC regulation 1907/2006 (REACH).

Directive 2000/532/EC.

EC Regulation 1272/2008 (CLP).

Health and Safety Authority (S.I. No. 619 of 2001).

According to EU regulation 1907/2006 (REACH)

Restrictions for application:

Seveso directive: 96/82/EC: People under the age of 18 may not carry out any work causing harmful exposure to this product. People above the age of 15 are exempted this rule, if the product is a part of an education/training.

Demands for specific education:

A thorough knowledge of this safety data sheet is a prerequisite.

Additional labelling:

No data.

15.2. Chemical safety assessment

Chemical safety assessment has been performed for the following substances: CAS no.: 86290-81-5: Gasoline.

SECTION 16: Other information

Other information:

The user must be instructed in the proper work procedure and be familiar with the contents of this SDS.

Regarding the use restrictions, see section 15.

This document contains important information to ensure the safe storage, handling and use of this product. The information in this document should be made available to people in your organization responsible for advising on safety matters.

Abbreviations and acronyms used:

STOT: Specific Target Organ Toxicity.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

NOEC: No Observed Effect Concentration.

NOAEL: No-observed-adverse-effect level.

PBT: Persistent, Bioaccumulative and Toxic.

vPvB: Very Persistent and Very Bioaccumulative.

Full text of H-phrases as mentioned in section 2+3:

H224 - Extremely flammable liquid and vapour.

H225 - Highly flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H336 - May cause drowsiness or dizziness.

H340 - May cause genetic defects.

H350 - May cause cancer.

H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child.

H411 - Toxic to aquatic life with long lasting effects.

Other

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

Important literature references and data sources:

Current legislation. Information from suppliers of raw materials. CONCAWE-report no.12/08 Hazard classification and labelling of petroleum substances in the European Economic Area 2012.

Exposure scenarios enclosed.

<https://circlek.chemicontrol.dk/Download/Exposure/-3968999993>

Minor changes have been made in following sections:

New SDS.



According to EU regulation 1907/2006 (REACH)

This safety data sheet replaces version:
New SDS.

Information in this safety data sheet (SDS) is based on the information we had at the time of preparation of the SDS, and they have been under the assumption that the product is used under the prescribed conditions and in accordance with the information specified on the packaging or in technical literature. Any other use of the product, if necessary, along with other products or processes is at the user's own risk.